

Portable Tool Transformers



Portable Tool Transformer P33/2



Portable Tool Transformer P50/3



Portable Tool Transformer P15/

PORTABLE TOOL TRANSFORMER

	PORTABLE TOOL TRANSFORMER	
	PRODUCT	1.5 KVA TRANSFORMER
	TYPE	ISOLATION TRANSFORMER
	MODEL NO	P15/2
	SAFETY LEVEL	Class I
	IP LEVEL	IP44
	SAFETY CERTIFICATES	CE
	RoHS DIRECTIVE	COMPLIANT
MATERIAL	CASE	GLASS REINFORCED PLASTIC (GRP)
	LID	GLASS REINFORCED PLASTIC (GRP)
ELECTRICAL	INPUT VOLTAGE	220V AC 1 PHASE
	OUTPUT VOLTAGE	110V AC (55-0-55V) CTE
	FREQUENCY	50/60Hz
	CONT. RATING	900VA
	TOOL RATING	1500VA
MAINS INPUT CABLE	CABLE	1.5 MM ² 3 CORE RUBBER CABLE – H07RN-F
	DIMENSIONS	2000 MM IN LENGTH
	COLOUR	BLACK
OUTPUT SOCKETS	2x110V 16AMP 2P+E, IP44 RATED to EN 60309	
PLUG	230V 13A BS UK 3 PIN PLUG (TO BS 1363/A) WITH 13A FUSE (TO BS 1362)	
CARTON BOX DIMENSION	QTY. OF EACH CARTON	1
	NET WEIGHT	10.4KG
	GROSS WEIGHT	10.8KG
	OUTER BOX DIMENSION	28X19X26CM

RoHS Certificate of Compliance

Statement of Conformity

PORTABLE TOOL TRANSFORMER

	PORTABLE TOOL TRANSFORMER	
	PRODUCT	3.3 KVA TRANSFORMER
	TYPE	ISOLATION TRANSFORMER
	MODEL NO	P33/2
	SAFETY LEVEL	Class I
	IP LEVEL	IP44
	SAFETY CERTIFICATES	CE
	RoHS DIRECTIVE	COMPLIANT
MATERIAL	CASE	GLASS REINFORCED PLASTIC (GRP)
	LID	GLASS REINFORCED PLASTIC (GRP)
ELECTRICAL	INPUT VOLTAGE	230V AC 1 PHASE
	OUTPUT VOLTAGE	110V AC (55-0-55V) CTE
	FREQUENCY	50/60Hz
	CONT. RATING	1650VA
	TOOL RATING	3000VA
MAINS INPUT CABLE	CABLE	1.5 MM ² 3 CORE RUBBER CABLE – H07RN-F
	DIMENSIONS	2000 MM IN LENGTH
	COLOUR	BLACK
OUTPUT SOCKETS	2X110V 16A 2P+E, IP44 RATED to EN 60309	
PLUG	230V 13A BS UK 3 PIN PLUG (TO BS 1363/A) WITH 13A FUSE (TO BS 1362)	
CARTON BOX DIMENSION	QTY. OF EACH CARTON	1
	NET WEIGHT	17KG
	GROSS WEIGHT	17.5KG
	OUTER BOX DIMENSION	210X250X275 MM

RoHS Certificate of Compliance

Statement of Conformity

PORTABLE TOOL TRANSFORMER

	PORTABLE TOOL TRANSFORMER	
	PRODUCT	5 KVA TRANSFORMER
	TYPE	ISOLATION TRANSFORMER
	MODEL NO	P50/3
	SAFETY LEVEL	Class I
	IP LEVEL	IP44
	SAFETY CERTIFICATES	CE
	RoHS DIRECTIVE	COMPLIANT
MATERIAL	CASE	GLASS REINFORCED PLASTIC (GRP)
	LID	GLASS REINFORCED PLASTIC (GRP)
ELECTRICAL	INPUT VOLTAGE	220V AC 1 PHASE
	OUTPUT VOLTAGE	110V AC (55-0-55V) CTE
	FREQUENCY	50/60Hz
	CONT. RATING	2800VA
	TOOL RATING	5000VA
MAINS INPUT CABLE	CABLE	2.5 MM ² 3 CORE RUBBER CABLE – H07RN-F
	DIMENSIONS	2000 MM IN LENGTH
	COLOUR	BLACK
OUTPUT SOCKETS	2X110V 16A, 1X110V 32A 2P+E, IP44 RATED to EN 60309	
PLUG	230V 13A BS UK 3 PIN PLUG (TO BS 1363/A) WITH 13A FUSE (TO BS 1362)	
CARTON BOX DIMENSION	QTY. OF EACH CARTON	1
	NET WEIGHT	30.5KG
	GROSS WEIGHT	31.5KG
	OUTER BOX DIMENSION	39.5X35.5X34 CM

RoHS Certificate of Compliance

Statement of Conformity